

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 111-004559 WOOD FILLER GEL  
Print date: 05.11.2019 Revision date: 05.11.2019  
Version: 15.0 Issue date: 05.11.2019

EN  
Page 1 / 9

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1. **product identifiers**

Article No. (manufacturer/supplier) 111-004559  
Trade name/designation WOOD FILLER GEL

1.2. **Relevant identified uses of the substance or mixture and uses advised against**

1.3. **Details of the supplier of the safety data sheet**

**supplier (manufacturer/importer/downstream user/distributor)**

Debal Coatings NV  
Industrieweg 29 Telephone: +32 51 30 11 40  
B-8800Beveren-Roeselare Telefax: +32 (0)51 31 26 48

**Dept. responsible for information:**

Labo:  
E-mail (competent person) info@debalcoatings.be

1.4. **Emergency telephone:**

Emergency telephone: +32 51 30 11 40  
(opening hours Monday to Friday from 8:00 am to 4:30 pm)

**SECTION 2: Hazards identification**

2.1. **Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.

2.2. **Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



**Danger**

**Hazard statements**

H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H336 May cause drowsiness or dizziness.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 Wear protective gloves and eye/face protection.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER or doctor/ physician.  
P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.

**Hazard components for labelling**

butan-1-ol  
Acetone

**Supplemental Hazard information (EU)**

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. **Other hazards**

No information available.

**SECTION 3: Composition / information on ingredients**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 111-004559 WOOD FILLER GEL  
Print date: 05.11.2019 Revision date: 05.11.2019  
Version: 15.0 Issue date: 05.11.2019

EN  
Page 2 / 9

### 3.2. Mixtures

#### Description

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Designation classification // Remark	Wt %
200-662-2 67-64-1 606-001-00-8	01-2119471330-49 Acetone Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	25 - 50
205-500-4 141-78-6 607-022-00-5	01-2119475103-46 Ethyl acetate Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	20 - 25
200-751-6 71-36-3 603-004-00-6	01-2119484630-38 butan-1-ol Flam. Liq. 3 H226 / Acute Tox. 4 H302 / STOT SE 3 H335 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 / STOT SE 3 H336	12,5 - 20
204-658-1 123-86-4 607-025-00-1	01-2119485493-29 n-butyl acetate Flam. Liq. 3 H226 / STOT SE 3 H336	12,5 - 20
603-037-00-6	cellulose nitrate Expl. 1.1 H201	5 - 10
200-661-7 67-63-0 603-117-00-0	01-2119457558-25 propan-2-ol Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	2,5 - 5

#### Additional information

Full text of classification: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

#### Unsuitable extinguishing media

strong water jet

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 111-004559 WOOD FILLER GEL  
Print date: 05.11.2019 Revision date: 05.11.2019  
Version: 15.0 Issue date: 05.11.2019

EN  
Page 3 / 9

**5.2. Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

**5.3. Advice for firefighters**

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

**6.3. Methods and material for containment and cleaning up**

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

**6.4. Reference to other sections**

Observe protective provisions (see section 7 and 8).

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advices on safe handling**

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

**Further information**

Vapours are heavier than air. Vapours form explosive mixtures with air.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Storage in accordance with the Ordinance on Industrial Safety and Health (BetRSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

**Hints on joint storage**

Keep away from strongly acidic and alkaline materials as well as oxidizers.

**Further information on storage conditions**

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

**7.3. Specific end use(s)**

Observe technical data sheet. Observe instructions for use.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limit values:**

Acetone

INDEX No. 606-001-00-8 / EC No. 200-662-2 / CAS No. 67-64-1

WEL, TWA: 1210 mg/m<sup>3</sup>; 500 ppm

WEL, STEL: 3620 mg/m<sup>3</sup>; 1500 ppm

\*

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 111-004559 WOOD FILLER GEL  
Print date: 05.11.2019 Revision date: 05.11.2019  
Version: 15.0 Issue date: 05.11.2019

EN  
Page 4 / 9

Ethyl acetate  
INDEX No. 607-022-00-5 / EC No. 205-500-4 / CAS No. 141-78-6

WEL, TWA: 734 mg/m<sup>3</sup>; 200 ppm  
WEL, STEL: 1468 mg/m<sup>3</sup>; 400 ppm

butan-1-ol  
INDEX No. 603-004-00-6 / EC No. 200-751-6 / CAS No. 71-36-3

WEL, STEL: 154 mg/m<sup>3</sup>; 50 ppm

n-butyl acetate  
INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

MEL/OES, TWA: 724 mg/m<sup>3</sup>; 150 ppm  
MEL/OES, STEL: 966 mg/m<sup>3</sup>; 200 ppm

propan-2-ol  
INDEX No. 603-117-00-0 / EC No. 200-661-7 / CAS No. 67-63-0

WEL, TWA: 999 mg/m<sup>3</sup>; 400 ppm  
WEL, STEL: 1250 mg/m<sup>3</sup>; 500 ppm

**Additional information**

TWA : long-term occupational exposure limit value  
STEL : short-term occupational exposure limit value  
Ceiling : peak limitation

**DNEL:**

propan-2-ol  
INDEX No. 603-117-00-0 / EC No. 200-661-7 / CAS No. 67-63-0

DNEL long-term dermal (systemic), Workers: 888 mg/kg  
DNEL long-term inhalative (systemic), Workers:  
DNEL long-term oral (repeated), Consumer: 26 mg/kg  
DNEL long-term dermal (systemic), Consumer: 319 mg/kg  
DNEL long-term inhalative (systemic), Consumer: 89 mg/m<sup>3</sup>

n-butyl acetate  
INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

DNEL acute inhalative (local), Workers: 960 mg/m<sup>3</sup>  
DNEL acute inhalative (systemic), Workers: 960 mg/m<sup>3</sup>  
DNEL long-term inhalative (local), Workers: 480 mg/m<sup>3</sup>  
DNEL long-term inhalative (systemic), Workers: 480 mg/m<sup>3</sup>  
DNEL short-term oral (acute), Consumer: 102,34 mg/kg  
DNEL acute inhalative (local), Consumer: 859,7 mg/m<sup>3</sup>  
DNEL acute inhalative (systemic), Consumer: 859,7 mg/m<sup>3</sup>  
DNEL long-term inhalative (local), Consumer: 102,34 mg/m<sup>3</sup>

**PNEC:**

propan-2-ol  
INDEX No. 603-117-00-0 / EC No. 200-661-7 / CAS No. 67-63-0

PNEC aquatic, freshwater: 140,9 mg/l  
PNEC aquatic, marine water: 140,9 mg/l  
PNEC aquatic, intermittent release: 140,9 mg/l  
PNEC sediment, freshwater: 552 mg/kg  
PNEC sediment, marine water: 552 mg/kg  
PNEC, soil: 28 mg/kg  
PNEC sewage treatment plant (STP): 2251 mg/l

n-butyl acetate  
INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

PNEC aquatic, freshwater: 0,18 mg/l  
PNEC aquatic, marine water: 0,018 mg/l  
PNEC aquatic, intermittent release: 0,36 mg/l  
PNEC sediment, freshwater: 0,981 mg/kg  
PNEC, soil: 0,0903 mg/kg  
PNEC sewage treatment plant (STP): 35,6 mg/l

8.2. **Exposure controls**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 111-004559  
Print date: 05.11.2019  
Version: 15.0

WOOD FILLER GEL  
Revision date: 05.11.2019  
Issue date: 05.11.2019

EN  
Page 5 / 9

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

**Personal protection equipment**

**Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

**Hand protection**

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

**Eye/face protection**

Wear closely fitting protective glasses in case of splashes.

**Body protection**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

**Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

**Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

**SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

**Appearance:**

**Physical state:** Liquid  
**Colour:** refer to label

**Odour:** characteristic

**Odour threshold:** not applicable

**pH at 20 °C:** not applicable

**Melting point/freezing point:** not applicable

**Initial boiling point and boiling range:** not determined

**Flash point:** 2 °C

**Evaporation rate:** not applicable

**flammability**

**Burning time (s):** not applicable

**Upper/lower flammability or explosive limits:**

**Lower explosion limit:** not determined

**Upper explosion limit:** not determined

**Vapour pressure at 20 °C:** not determined

**Vapour density:** not applicable

**Relative density:**

**Density at 20 °C:** 0,90 g/cm<sup>3</sup>

**Solubility(ies):**

**Water solubility (g/L) at 20 °C:** partially soluble

**Partition coefficient: n-octanol/water:** see section 12

**Auto-ignition temperature:** not determined

**Decomposition temperature:** not applicable

**Viscosity at 20 °C:** 60 s 6 mm

Method: DIN 53211

**Explosive properties:** not applicable

**Oxidising properties:** not applicable

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 111-004559  
Print date: 05.11.2019  
Version: 15.0

WOOD FILLER GEL  
Revision date: 05.11.2019  
Issue date: 05.11.2019

EN  
Page 6 / 9

9.2. **Other information**

**Solid content (%):** 13,51 Wt %  
**solvent content:**  
**Organic solvents:** 86,5 Wt %  
**Water:** 0,0 Wt %

**SECTION 10: Stability and reactivity**

10.1. **Reactivity**

No information available.

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. **Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**

not applicable

10.6. **Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

**SECTION 11: Toxicological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

11.1. **Information on toxicological effects**

**Acute toxicity**

Based on available data, the classification criteria are not met.

**Skin corrosion/irritation; Serious eye damage/eye irritation**

Causes skin irritation.

Causes serious eye damage.

**Respiratory or skin sensitisation**

Based on available data, the classification criteria are not met.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Based on available data, the classification criteria are not met.

**STOT-single exposure; STOT-repeated exposure**

May cause drowsiness or dizziness.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Practical experience/human evidence**

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

**Overall Assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

**SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

12.1. **Toxicity**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 111-004559 WOOD FILLER GEL  
Print date: 05.11.2019 Revision date: 05.11.2019  
Version: 15.0 Issue date: 05.11.2019

EN  
Page 7 / 9

Based on available data, the classification criteria are not met.

**12.2. Persistence and degradability**

Toxicological data are not available.

**12.3. Bioaccumulative potential**

Toxicological data are not available.

**12.4. Mobility in soil**

Toxicological data are not available.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Appropriate disposal / Product Recommendation**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**List of proposed waste codes/waste designations in accordance with EWC**

080111\* Waste paint and varnish containing organic solvents or other dangerous substances

\*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

**Appropriate disposal / Package Recommendation**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**14.1. UN number**

UN 1263

**14.2. UN proper shipping name**

Land transport (ADR/RID): Verferwante produkten

Sea transport (IMDG): PAINT

Air transport (ICAO-TI / IATA-DGR): Paint

**14.3. Transport hazard class(es)**

3

**14.4. Packing group**

Land transport (ADR/RID): III

for packages > 450 litres: II

Sea transport (IMDG): III

for packages > 450 litres: II

Air transport (ICAO-TI / IATA-DGR): III

for packages > 30 litres: II

**14.5. Environmental hazards**

Land transport (ADR/RID) not applicable

Marine pollutant not applicable

**14.6. Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**Further information**

**Land transport (ADR/RID)**

tunnel restriction code E  
for packages > 450 litres: D/E

**Sea transport (IMDG)**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 111-004559 WOOD FILLER GEL  
Print date: 05.11.2019 Revision date: 05.11.2019  
Version: 15.0 Issue date: 05.11.2019

EN  
Page 8 / 9

EmS-No. F-E, S-E

14.7. **Transport in bulk according to Annex II of Marpol and the IBC Code**  
not applicable

**SECTION 15: Regulatory information**

15.1. **Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Directive 2010/75/EU on industrial emissions**

VOC-value (in g/L): 743,036

**National regulations**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

15.2. **Chemical Safety Assessment**

**For the following substances of this mixture a chemical safety assessment has been carried out:**

EC No. CAS No.	Designation	REACH No.
200-662-2 67-64-1	Acetone	01-2119471330-49
205-500-4 141-78-6	Ethyl acetate	01-2119475103-46
200-751-6 71-36-3	butan-1-ol	01-2119484630-38
204-658-1 123-86-4	n-butyl acetate	01-2119485493-29
200-661-7 67-63-0	propan-2-ol	01-2119457558-25

**SECTION 16: Other information**

**Full text of classification in section 3**

Flam. Liq. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
STOT SE 3 / H336	STOT-single exposure	May cause drowsiness or dizziness.
Flam. Liq. 3 / H226	Flammable liquids	Flammable liquid and vapour.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Expl. 1.1 / H201	Explosives	Explosive; mass explosion hazard.

**Classification procedure**

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2	Flammable liquids	On basis of test data.
Skin Irrit. 2	Skin corrosion/irritation	Calculation method.
Eye Dam. 1	Serious eye damage/eye irritation	Calculation method.
STOT SE 3	STOT-single exposure	Calculation method.

**Abbreviations and acronyms**

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2015/830



Article No.: 111-004559 WOOD FILLER GEL  
Print date: 05.11.2019 Revision date: 05.11.2019  
Version: 15.0 Issue date: 05.11.2019

EN  
Page 9 / 9

---

IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

**Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

\* Data changed compared with the previous version